

KAM 98

Single Port Multi-Mode Digital Controller

Built on the proud heritage established by the KAM and KAM Plus, the KAM '98 offers more flexibility to the digital operator. KAM '98 is a single port unit that can be used on either HF or VHF frequencies. HF operators can now enjoy 1200 bps communications on 10 meters, or copy WEFAX feeds without cable swapping. Telemetry and remote control operations are now possible, through the use of two A/D inputs accessed through an AUX port and two control line outputs.



KAM 98 OPERATIONS

- GTOR
- PACTOR
- AMTOR, ARQ, FEC, SELFEC,
- CCIR 476 & 625
- PACKET 300 or 1200 bps
- RTTY
- NAVTEX/AMTEX
- ASCII
- WEFAX
- EMWIN
- HF E-Mail
- CW
- GPS NMEA-0183 compatible
- TELEMETRY
- REMOTE CONTROL
- REMOTE SYSOP ACCESS
- HOST Mode
- KISS Mode

KAM 98 OPTIONS

- 120 V ac to 12 V dc power cube
- 512 k memory expansion chip

The Kantronics KAM '98 is a versatile digital mode communicator engineered for years of dependable performance. Kantronics has been a pioneer in digital communications, taking care to listen to the suggestions of digital operators, like you.

